



# POWER WALLBOX

## 11.0 | 22.0

### SMART EV-CHARGER

- Intelligent and configurable load management
- Keyswitch for easy program selection
- Operating states are visualized via LED display
- Visualization via web interface
- Integrated DC leakage current detection requires only RCD type A
- Connection cable with type II plug

Power Wallbox	11.0	22.0
---------------	------	------

#### GENERAL

Grid connection	3-phase 400 V	3-phase 400 V
Nominal voltage	400 V	400 V
Rated current	16 A	32 A
Maximum charge	11 kW	22 kW
Connector type II	4 m cable twisted	5 m cable straight
Protective switchgear	LS 16 A 3p	LS 32 A 3p
DC leakage current detection	electronic 6 mA	electronic 6 mA
Conductor cross section of supply line	min. 2,5 mm <sup>2</sup> / max. 10mm <sup>2</sup>	min. 6,0 mm <sup>2</sup> / max. 10mm <sup>2</sup>
Power Storage interface	LAN	
Colour	white	
Dimensions (height x width x depth)	477x400x164 mm	
Complementary functions	web server, load recording, energy meter, load management, operating states via LED display	
RFID functionality	optional	

#### SECURITY / STANDARDS

Safety class	II
IP degree of protection	44
Certificates	IEC 61851-1, IEC 61851-22
Warranty	2 years

© RCT Power GmbH ■ revisions reserved ■ version 01/2020